









Ampère	Poles	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	> 50 - 500 V 100 - 300 Hz	> 50 - 500 V over 300 - 500 Hz		
		3pole 4h 4pole 4h 5pole 4h	3pole 6h 4pole 9h 5pole 9h	3pole 9h 4pole 6h 5pole 6h	3pole 7h 4pole 7h 5pole 7h	3pole 10h 4pole 10h 5pole 10h	3pole 2h 4pole 2h 5pole 2h		g


Part numbers


	16	3	610 304	610 306	610 309				10	126	
	16	4	610 404	610 409	610 406	610 407	610 410	610 402	10	164	
	16	5	610 504	610 509	610				10/60	177	
	16	5			610 NI	<i>(NI = with nickel plated contacts & glass-fibre reinforced enclosure)</i>					
	16	5			610 PH	<i>(PH = with phase inverter)</i>				10	184
	16	5			610 PHNI	<i>(PHNI = with phase inverter, nickel plated contacts and glass-fibre reinforced enclosure)</i>					
	32	3	630 304	630 306	630 309				10	219	
	32	4	630 404	630 409	630 406	630 407	630 410	630 402	10	237	
	32	5	630 504	630 509	630				10	256	
	32	5			630 NI	<i>(NI = with nickel plated contacts & glass-fibre reinforced enclosure)</i>					
	32	5			630 PH	<i>(PH = with phase inverter)</i>				10	264


630 **Wall mount appliance inlets**  IP 44, external fixing means, 1 top cable entry

	16	4	616 404	616 409	616 406	616 407	616 410	616 402	5	323
	16	5	616 504	616 509	616				5	352
	32	3	636 304	636 306	636 309				5	349
	32	4	636 404	636 409	636 406	636 407	636 410	636 402	5	372
	32	5	636 504	636 509	636				5	399


636 **Wall mount appliance inlets**  IP 44, internal fixing means, 2 cable entries top & bottom

	16	3	611 304	611 306	611 309				10	122	
	16	4	611 404	611 409	611 406	611 407	611 410	611 402	10	176	
	16	5	611 504	611 509	611				10	207	
	16	5			611 PH	<i>(PH = with phase inverter)</i>				10	205
	16	5			611 PHNI	<i>(PHNI = with phase inverter, nickel plated contacts and glass-fibre reinforced enclosure)</i>					
	32	3	631 304	631 306	631 309				10	230	
	32	4	631 404	631 409	631 406	631 407	631 410	631 402	10	293	
	32	5	631 504	631 509	631				10	276	
	32	5			631 NI	<i>(NI = with nickel plated contacts & glass-fibre reinforced enclosure)</i>					
	32	5			631 PH	<i>(PH = with phase inverter)</i>				10	283
	32	5			631 PHNI	<i>(PHNI = with phase inverter, nickel plated contacts and glass-fibre reinforced enclosure)</i>					

631 **Panel mount appliance inlets** IP 44  , right-angled, flange screwed on


	16	3	615 304	615 306	615 309				10	94	
	16	4	615 404	615 409	615 406	615 407	615 410	615 402	10	131	
	16	5	615 504	615 509	615				10	145	
	16	5			615 PH	<i>(PH = with phase inverter)</i>				10	145
	32	3	635 304	635 306	635 309				10	150	
	32	4	635 404	635 409	635 406	635 407	635 410	635 402	10	166	
	32	5	635 504	635 509	635				10	191	
	32	5			635 PH	<i>(PH = with phase inverter)</i>				10	191

635 **Panel mount appliance inlets** IP 44  , straight, flange screwed on

	16	3	612 306 <i>(white)</i>						1	242
	16	3	613 306 <i>(brown)</i>	<i>(fastening frame also serving as template for drilling holes)</i>					1	242
	16	3	614 306 <i>(black)</i>						1	242

612306 **Caravan built-in appliance inlet, IP 44** 



Ampère	Poles	110 V 50 a. 60 Hz	230 V 50 a. 60 Hz	400 V 50 a. 60 Hz	500 V 50 a. 60 Hz	> 50 - 500 V 100 - 300 Hz	> 50 - 500 V over 300 - 500 Hz		
		3pole 4h 4pole 4h 5pole 4h	3pole 6h 4pole 9h 5pole 9h	3pole 9h 4pole 6h 5pole 6h	3pole 7h 4pole 7h 5pole 7h	3pole 10h 4pole 10h 5pole 10h	3pole 2h 4pole 2h 5pole 2h		

Part numbers



638	16	3	618 304	618 306	618 309				5	357
		4	618 404	618 409	618 406	618 407	618 410	618 402	5	328
		5	618 504	618 509	618				5	357
	32	3	638 304	638 306	638 309				5	421
		4	638 404	638 409	638 406	638 407	638 410	638 402	5	427
		5	638 504	638 509	638				5	463

Wall mount appliance inlets IP 67 , internal fixing



639	16	3	619 304	619 306	619 309				10	195	
		4	619 404	619 409	619 406	619 407	619 410	619 402	10	206	
		5	619 504	619 509	619				10	217	
		619 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)									
		5									
	32	3	639 304	639 306	639 309				5	223	
		4	639 404	639 409	639 406	639 407	639 410	639 402	5	259	
		5	639 504	639 509	639				5	295	
		639 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)									
		5									
	63	3	669 304	669 306	669 309				5	525	
		4	669 404	669 409	669 406	669 407	669 410	669 402	5	569	
		5	669 504	669 509	669				5	613	
		669 NI (NI = with nickel plated contacts & glass-fibre reinforced enclosure)									
		5									


Panel mount appliance inlets IP 67 , right-angled, flange screwed on



668	63	3	668 304	668 306	668 309				2	825
		4	668 404	668 409	668 406	668 407	668 410	668 402	2	827
		5	668 504	668 509	668				2	891

Wall mount appliance inlets IP 67 , external fixing, 1 top cable entry



678	125	3	678 304	678 306	678 309				1	2700	
		4	678 404	678 409	678 406	678 407	678 410	678 402	1	3005	
		5	678 504	678 509	678				1	3800	
	125	3	678 304 OK	678 306 OK	678 309 OK				1	860	
		4	678 404 OK	678 409 OK	678 406 OK	678 407 OK	678 410 OK	678 402 OK	1	1455	
		5	678 504 OK	678 509 OK	678 OK	OK = without terminal block set			1	2250	
	678 Wall mount appliance inlets IP 67  , internal fixing, with terminal block set										



679	125	3	679 304	679 306	679 309				2	673
		4	679 404	679 409	679 406	679 407	679 410	679 402	2	910
		5	679 504	679 509	679				2	1147

Panel mount appliance inlets IP 67 , straight, flange screwed on